



HD SERIES

power beyond the standards

Enjoy your choice:

OSA series increase with a new primary demolition series which is aimed to the professionals who need ever higher performance without sacrificing solidity and ease of use.

With this new concept, OSA brings the following features to the market:

- ability to crush and break down special concrete structures;
- new cylinders design;
- new claws optimized for the new function;
- overall lighter machines;
- increased strength of the jaw at the tip.

HD SERIES

DEMOLITION CRUSHERS

HD SERIES	U.M.	HD 1000	HD 1500	HD 1800	HD 2000	HD 2500	HD 4000	HD 5000	HD 6000	HD 8000	HD 12000
APERTURA (A)	mm	480	660	765	892	1030	1260	1400	1540	1700	2140
OPENING (A)	in.	19	26	30	35	41	50	55	61	67	84
LUNGHEZZA (B)	mm	1700	1740	2150	2190	2235	2750	2800	2920	3100	3750
LENGTH (B)	in.	67	69	85	86	88	108	110	115	122	148
LARGHEZZA (P)	mm	377	378	430	559	565	750	890	980	1080	1200
WIDTH (P)	in.	15	15	17	22	22	30	35	39	43	47
PESO ESCAVATORE	Ton	12/16	16/22	22/30	35/50	35/50	45/60	50/65	60/80	80/100	90/150
EXCAVATOR WEIGHT	lbs	24000/ 32000	32000/ 44000	44000/ 60000	70000/ 100000	70000/ 100000	80000/ 120000	100000/ 130000	120000/ 160000	160000/ 200000	180000/ 300000
PESO	Kg	1150	1400	1900	2200	2580	3800	4800	5800	7900	11950
EQUIPMENT WEIGHT	lbs	2535	3086	4189	4850	5688	8378	10582	12787	17416	26345
PRESSIONE OLIO	Bar	300	310	320	320	320	340	340	340	340	340
OIL PRESSURE	psi	4351	4496	4641	4641	4641	4931	4931	4931	4931	4931
PORTATA OLIO	L/min	200/220	220/240	240/280	300/340	300/340	300/380	350/400	380/450	400/500	450/700
OIL CAPACITY	gal/min	53/58	58/63	63/74	79/90	79/90	79/100	92/106	100/119	106/132	119/185
PRESSIONE OLIO ROTAZIONE	Bar	140	140	140	140	140	140	140	140	140	140
ROTATION OIL PRESSURE	psi	2030	2030	2030	2030	2030	2030	2030	2030	2030	2030
PORTATA OLIO ROTAZIONE	L/min	30	30	30	30	30	30	30	30	60	90
ROTATION OIL CAPACITY	gal/min	8	8	8	8	8	8	16	16	16	24
F1	ton	27	57	120	180	180	210	250	310	385	450
F2	ton	57	180	450	695	720	830	995	1230	1480	1680

